



**QUICK CHILL POWER PAKS**  
Air Cooled



JOB	
AREA	
ITEM NO.	
MODEL NO.	

		MODELS			
Compressor Size		1/3 HP	1/2 HP	3/4 HP	1-1/2 HP
# of Circulating Pumps	1	4404QC	4410QC	4414QC	4420QC
	2		4410QC-2	4414QC-2	4420QC-2
	3				4420QC-3

**KEY PRODUCT FEATURES AND BENEFITS**

- Option of 1/3, 1/2, or 3/4 HP at 120V and 1-1/2 HP at 230V models
- Digital display provides temperature readout and allows for temperature adjustments
- High efficiency, compact heat exchanger provides superior cooling for longer beer runs
- 70 gallon per hour glycol pump ensures beverages stay cold
- Top-mounted, close-coupled pump and 1/3 HP ball bearing motor assembly is easily serviceable
- Factory pre-mixed glycol guarantees superior cooling performance
- Highly efficient with 1.75 gallon glycol bath
- Power Pak stand and legs available for off-the-floor mounting

**ACCESSORIES**

MODEL NOS.	DESCRIPTION
4408SS	Wall Bracket for 4404 & 4410 only
57782	Set of four adjustable legs
61790A2	Dual tier rack
61790A3	Triple tier rack
C22296A-20	Cord Kit for 120V single pump Power Paks only (Field Installed)
C21499BSS	Stainless Steel Table Stand
61468	Overflow Bottle Kit
63299-1	Food Grade Glycol Pre-Mix (1 gallon)



**QUICK CHILL POWER PAKS**  
Air Cooled

MODEL NUMBERS - 4404QC, 4410QC, 4410QC-2, 4414QC, 4414QC-2, 4420QC, 4420QC-2, 4420QC-3

MODEL NOS.	4404QC	4410QC	4410QC-2	4414QC	4414QC-2	4420QC	4420QC-2	4420QC-3	
<b>DIMENSIONS: EXTERIOR (mm)</b>	<b>Length "A"</b>	24-1/4" (616)					26-3/4" (680)		
	<b>Width "B"</b>	17-1/4" (439)					20-1/4" (515)		
	<b>Height "C"</b>	25-1/2" (648)					31" (788)		
	*A minimum of six inches of clearance should be allowed around the entire unit for proper performance. Additional Clearance should be considered for above the unit and in front of the unit for serviceability.								
<b>ELECTRICAL</b>	<b>Voltage</b>	120V				115-208/230V **			
	<b>Frequency</b>	60 Hz							
	<b>Phase</b>	1 Ø							
	<b>RLA (Rated Load Amps)</b>	14.4	15.7	21.8	20.6	26.2	21.9	24.7	27.5
	<b>MCA (Min. Circuit Ampacity)</b>	16.4	18.0	24.1	24.0	29.6	26.6	29.2	32.0
	<b>MOCP (Max. Over-Current Protection)</b>	20	25	30	35	40	40	45	50
<b>COMPRESSOR (Horse Power)</b>	1/3	1/2		3/4		1-1/2			
<b>EVAPORATOR RATING @ 20°F (BTUH)</b>	2550	3800		6000		12000			
<b>HEAT of REJECTION MAX (BTUH)</b>	4080	6080		9600		19200			
<b>REFRIGERATION</b>	Constant Pressure Expansion Valve, Condensing Unit with Service Valves								
<b>REFRIGERANT (TYPE)</b>	R-134a								
<b>REFRIGERANT CHARGE</b>	14.0 oz/397g	12.0 oz/340g		14.0 oz/397g		16.0 oz/454g			
<b>SHIPPING WEIGHT LBS (kg)</b>	140 (64)	138 (63)	150 (69)	167 (76)	180 (82)	217 (99)	230 (105)	245 (112)	
<b>CABINET</b>	Black Vinyl Clad Galvanized Steel								
<b>CIRCULATING PUMP</b>	70 GPH / 80 PSIG (MAX)								
<b>RESERVOIR CAPACITY</b>	1.75 Gallons								
<b>GLYCOL CONCENTRATION</b>	30%								
<b>OPTIONAL ACCESSORIES (Sold Separately)</b>	<ul style="list-style-type: none"> <li>• C22296A-20 - Power Cord Kit for 4404QC &amp; 4410QC Single Pump Units Only (NEMA 5-20P)</li> <li>• 57782 - Adjustable Legs (Set of 4)</li> <li>• 61468 - Overflow Bottle Kit</li> <li>• 63299-1 - Food Grade Glycol Pre-Mix (1 gallon)</li> <li>• 61790A2 - Dual Tier Rack</li> <li>• 61790A3 - Triple Tier Rack</li> <li>• C21499SS - Stainless Steel Table Stand</li> <li>• 4408SS - Wall Bracket for 4404QC &amp; 4410QC Only</li> </ul>								

\*\*4-WIRE AC POWER SOURCE REQUIRED  
AC - 115-208/240V, 60Hz, Split Single Phase  
(Ground, Neutral, Hot-Power, Hot-Power)



**QUICK CHILL POWER PAKS**  
Air Cooled

MODEL NUMBERS - 44040C, 44100C, 44100C-2, 44140C, 44140C-2, 44200C, 44200C-2, 44200C-3

